



## STATEMENT OF ACCEPTANCE OF CHOCKING RESIN

Certificate No. MATS/3782/1

This certificate is issued to the company named below. Based on the examination of the data submitted the product described is considered acceptable for use in constructions built under Lloyd's Register's survey. This acceptance is subject to Lloyd's Register being informed of any changes in or modifications to the product and the product being used in accordance with the manufacturer's instructions and with the relevant requirements of Lloyd's Register's Rules and Regulations.

Company PHILADELPHIA RESINS  
MONTGOMERYVILLE  
UNITED STATES OF AMERICA

Trade name CHOCKFAST ORANGE

Test data: Generated by Lloyd's Register EMEA Materials Laboratory

Approval for:

Maximum loading of 5.0 MPa where the chocking compound is post cured to a minimum temperature of 60°C for 16 hours.

Valid until 30 September 2012

Date 26 September 2007

**M Jogia**  
Surveyor to Lloyd's Register EMEA  
member of the Lloyd's Register Group

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.